

Plastic-Encapsulate Diodes

GENERAL PURPOSE PIN DIODE


FEATURES

- Low diode capacitance
- Low diode forward resistance

MARKING: A81

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



Top View
Marking Code: " "
Simplified outline SOD-323 and symbol

Maximum Ratings and Electrical Characteristics, Single Diode @Ta=25°C

Parameter	Symbol	Limit			Unit
Continuous Reverse Voltage	V _R	50			V
Continuous Forward Current	I _F	50			mA
Power Dissipation (Ta=90°C)	P _d	200			mW
Thermal Resistance Junction to Ambient	R _{θJA}	85			°C/W
Junction Temperature	T _j	150			°C
Storage Temperature	T _{STG}	-55~+150			°C

Electrical Ratings @Ta=25°C

Parameter	Symbol	Min	Typ	Max	Unit	Conditions
Continuous reverse voltage	V _R	50			V	I _R =10μA
Forward voltage	V _F			1.1	V	I _F =50mA
Reverse current	I _R			100	nA	V _R =50V
Diode capacitance	C _{d1}			0.91	pF	V _R =0V,f=1MHz
	C _{d2}			0.55	pF	V _R =1V,f=1MHz
	C _{d3}			0.35	pF	V _R =5V,f=1MHz
Diode forward resistance	r _D			40	Ω	I _F =0.5mA , f=100MHz; note1
	r _D			25	Ω	I _F =1mA , f=100MHz;note1
	r _D			5	Ω	I _F =10mA , f=100MHz;note1